

www.decrolux.com.au

Classic Series

Proven. Quality. Customisable

ALPHA 25W Adjustable Tracklight DALI

Track lighting is used because of its flexibility in positioning fittings, and removing or adding fittings to achieve the correct luminance levels. It can focus the viewer's attention onto a piece of art work or display.

Alpha S perfectly combines design and function. Optimized passive cooling system ensures low temperature and long lifetime of LED.

The Alpha Track Light is an architectural design, a high lighting quality, with optimised efficiency. Ideal for museums, art galleries, restaurants and reception areas.

Aluminium



SPECIFICATIONS

Material Specifications

Material
Finish
Dimensions
Adjustment
Application
Options
Warranty

Electrical Specifications

Power Supply Input Voltage **Connection Method**

Optic Specifications

Light Source **Beam Angle** CRI **Colour Deviation** Rated Lifetime (L80B20) Powder Coat Head 90mm Dia x 220mm(L) 90° tilt, 359° rotation 3-Wire Track Black Ring, Oblique Ring 5 Year Replacement

Integrated Tridonic Driver 700mA, DALI Dim 240V 3 Circuit Track. Sold Separately

28W Citizen LED
40° (18°/ 25° options)
90Ra
SDCM ≤ 3
50,000 Hrs

VARIATIONS

LC5106D-1 8	ALPHA 25W Tracklight, Black, 18°, DALI, 3000K, 1900lm
LC5106D-2 5	ALPHA 25W Tracklight, Black, 25°, DALI, 3000K, 1900lm
LC5300D-2 5	ALPHA 25W Tracklight, White, 25°, DALI, 3000K, 1900lm
LC5106D-4 0	ALPHA 25W Tracklight, Black, 40°, DALI, 3000K, 1900lm
LC5100D-4 0	ALPHA 25W Tracklight, White, 40°, DALI, 3000K, 1900lm
LC5101D-4 0	ALPHA 25W Tracklight, White, 40°, DALI, 4000K, 2000lm
LC5186D-4	ALPHA 25W Tracklight, Black, 40°, DALI, 4000K, 2000lm









0

1300 827 284 www.decrolux.com.au

Classic Series Proven. Quality. Customisable

