

ASTON 15W

Linear Pendant 565mm

Classic Series

Proven. Quality. Customisable

The ASTON 15W Linear Pendant 565mm is a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed. ASTON LED linear profile lights can be used in different situations with their flexibility and architectural design that blends into the environment. Common applications include colleges and universities, offices, and retail shops.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Dimensions	565mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 500mA Integrated LED Driver, Non-Dimmable
Options	0-10V Dimming Available
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	1545lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8114	ASTON 15W Linear Pendant, 565mm, Black, Non-Dim, 3000K
LC8115	ASTON 15W Linear Pendant, 565mm, White, Non-Dim, 3000K
LC8116	ASTON 15W Linear Pendant, 565mm, Black, Non-Dim, 4000K
LC8117	ASTON 15W Linear Pendant, 565mm, White, Non-Dim, 4000K