

ASTON 33W

Direct/Indirect Pendant 845mm

The ASTON 33W Direct/Indirect Pendant is an excellent lighting option for commercial spaces like offices and retail stores. The pendant provides ambient lighting while also allowing for focused lighting below the fixture. The 1.0mm aluminium housing and opal acrylic diffuser ensure durability and even light distribution, and the powdercoat finish gives it a sleek look. This options is ideal for those with higher ceilings and a need for both ambient and focused lighting.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	Powdercoat
Ingress Protection	IP44
Dimensions	845mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Integrated
Input Voltage	240V
Connection Method	Hard Wired

Optic Specifications

Light Source	22W Direct/ 11W Indirect, Samsung 2835 SMD
Nominal Lumens	2850lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8151	ASTON Linear Pendant, 22W Direct/ 11W Indirect, Black, Non-Dim, 3000K
LC8152	ASTON Linear Pendant, 22W Direct/ 11W Indirect, White, Non-Dim, 3000K
LC8153	ASTON Linear Pendant, 22W Direct/ 11W Indirect, Black, Non-Dim, 4000K
LC8154	ASTON Linear Pendant, 22W Direct/ 11W Indirect, White, Non-Dim, 4000K

Classic Series

Proven. Quality. Customisable

