Classic Series
Proven. Quality. Customisable

ASTON 38W
Linear Recessed 1405mm

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed. ASTON 38W Linear Recessed 1405mm is a simple, modular fitting which can be connected together. 5 Year Warranty.





IP40





SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1405mm(L) x 62mm(W) x 82mm(D)
Cutout	65mm(W)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver, non-Dimmable
Options	0-10V Dimming Available
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	3910lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8163	ASTON 38W Recessed Profile, 1405mm, Black, Non-Dim, 3000K
LC8164	ASTON 38W Recessed Profile, 1405mm, White, Non-Dim, 3000K
LC8165	ASTON 38W Recessed Profile, 1405mm, Black, Non-Dim, 4000K
LC8166	ASTON 38W Recessed Profile, 1405mm, White, Non-Dim, 4000K

Product design and technical data may be subject to change without prior notice.
Generated 29th Mar 2024 - © Decrolux

CE E582