

ASTON 38W


Linear Surface Mount 1405mm

Classic Series

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

ASTON 38W Linear Surface Mount 1405mm available in Black, White, 3000K and 4000K. Modular design, for easy installation.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Dimensions	1405mm(L) x 62mm(W) x 82mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver, Non-Dim
Options	0-10V Dimmable
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	3910lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8167	ASTON 38W Surface Mount Profile, 1405mm, Black, Non-Dim, 3000K
LC8168	ASTON 38W Surface Mount Profile, 1405mm, White, Non-Dim, 3000K
LC8169	ASTON 38W Surface Mount Profile, 1405mm, Black, Non-Dim, 4000K
LC8170	ASTON 38W Surface Mount Profile, 1405mm, White, Non-Dim, 4000K

