


# ASTON 45W

## Direct/Indirect Pendant 1125mm

The ASTON Linear Series offers a sleek and modern style that is perfect for commercial architecture. The 45W Linear Direct/Indirect Pendant 1125mm is ideal for offices with higher ceilings, providing both ambient light and focused illumination below the fitting. Made from high-quality materials, including aluminium housing with an opal acrylic diffuser and a powder coat finish, this pendant is durable and long-lasting. With a thin profile and a range of mounting options, the ASTON Linear Series is versatile and adaptable to any commercial space.



**IP44**



### SPECIFICATIONS

#### Material Specifications

|                           |                                                     |
|---------------------------|-----------------------------------------------------|
| <b>Material</b>           | 1.0mm Aluminium Housing, with Opal Acrylic Diffuser |
| <b>Finish</b>             | Powdercoat                                          |
| <b>Ingress Protection</b> | IP44                                                |
| <b>Dimensions</b>         | 1125mm(L) x 62mm(W) x 82mm(D)                       |
| <b>Suspension Length</b>  | 1200mm                                              |
| <b>Warranty</b>           | 5 Year Replacement                                  |

#### Electrical Specifications

|                      |                           |
|----------------------|---------------------------|
| <b>Power Supply</b>  | Osram LED Driver, Non-Dim |
| <b>Input Voltage</b> | 240V                      |

#### Optic Specifications

|                             |                                                             |
|-----------------------------|-------------------------------------------------------------|
| <b>Light Source</b>         | 30W Direct / 15W Indirect, Samsung LB281BA+ Series 2835 SMD |
| <b>Nominal Lumens</b>       | 3900lm                                                      |
| <b>CRI</b>                  | 80Ra                                                        |
| <b>Beam Angle</b>           | 120°                                                        |
| <b>Colour Deviation</b>     | SDCM ≤ 3                                                    |
| <b>Reported L70 (Hours)</b> | > 54,000 Hrs                                                |

### VARIATIONS

|               |                                                                             |
|---------------|-----------------------------------------------------------------------------|
| <b>LC8175</b> | ASTON Linear Pendant, 30W Direct/ 15W Indirect, Black, 120°, Non-Dim, 3000K |
| <b>LC8176</b> | ASTON Linear Pendant, 30W Direct/ 15W Indirect, White, 120°, Non-Dim, 3000K |
| <b>LC8177</b> | ASTON Linear Pendant, 30W Direct/ 15W Indirect, Black, 120°, Non-Dim, 4000K |
| <b>LC8178</b> | ASTON Linear Pendant, 30W Direct/ 15W Indirect, White, 120°, Non-Dim, 4000K |

**Classic Series**

Proven. Quality. Customisable

