

ASTON 52W


Linear Surface Mount 1965mm

Classic Series

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

ASTON 52W Linear Surface Mount 1965mm available in Black, White, 3000K and 4000K. Modular design, for easy installation.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Dimensions	1965mm(L) x 62mm(W) x 82mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver, Non-Dim
Options	0-10V Dimmable
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	5365lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8195	ASTON 52W Surface Mount Profile, 1965mm, Black, Non-Dim, 3000K
LC8196	ASTON 52W Surface Mount Profile, 1965mm, White, Non-Dim, 3000K
LC8197	ASTON 52W Surface Mount Profile, 1965mm, Black, Non-Dim, 4000K
LC8198	ASTON 52W Surface Mount Profile, 1965mm, White, Non-Dim, 4000K

