

ASTON 57W

Direct/Indirect Pendant 1405mm

Classic Series

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 57W Linear Direct/Indirect Pendant 1405mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1405mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Non-Dimmable
Input Voltage	240V

Optic Specifications

Light Source	38W Direct/ 19W Indirect, Epistar SMD 5630
Nominal Lumens	5,865lm (3910lm Down / 1955lm Up)
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8203	ASTON Linear Pendant, 38W Direct/ 19W Indirect, Black, Non-Dim, 3000K
LC8204	ASTON Linear Pendant, 38W Direct/ 19W Indirect, White, Non-Dim, 3000K
LC8205	ASTON Linear Pendant, 38W Direct/ 19W Indirect, Black, Non-Dim, 4000K
LC8206	ASTON Linear Pendant, 38W Direct/ 19W Indirect, White, Non-Dim, 4000K