

ASTON 67W

Direct/Indirect Pendant 1685mm

Classic Series

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 67W Linear Direct/Indirect Pendant 1685mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.

**IP40**

SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1685mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Non-Dimmable
Input Voltage	240V

Optic Specifications

Light Source	45W Direct/ 22W Indirect, Epistar SMD 5630
Nominal Lumens	6910lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8223	ASTON Linear Pendant, 45W Direct/ 22W Indirect, Black, Non-Dim, 3000K
LC8224	ASTON Linear Pendant, 45W Direct/ 22W Indirect, White, Non-Dim, 3000K
LC8225	ASTON Linear Pendant, 45W Direct/ 22W Indirect, Black, Non-Dim, 4000K
LC8226	ASTON Linear Pendant, 45W Direct/ 22W Indirect, White, Non-Dim, 4000K