

DEX 40W

Streetlight PE Cell

The Dex Streetlight Range are designed for exterior applications where design and style matters. Dex 40W Streetlight with PE Cell works by turning on automatically, once the light level drops below a certain level. Suited for carparks, boardwalks and common thoroughfares.



SPECIFICATIONS

Material Specifications

Material	Die-cast High Grade Aluminium
Colour	Corrosion Resistant Powder Coat, Black
Dimensions	620mm (L) x 260mm (W) x 101mm (H)
Spigot Size	53mm (Dia)
Ingress Protection	IP65
Impact Rating	IK09
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Integral Sosen Driver, Non-Dimmable
Benefits	In-built PE Cell
Connection Method	Hard Wiring
Input Voltage	240V
Operating Temperature (Ta)	-25°C to +45°C

Optic Specifications

Light Source	1pc 40W Epistar COB
Beam Angle	150°
Delivered Lumens	5114lm
Correlated Colour Temperature	5700K
CRI	80Ra
Rated Lifetime (L70B20)	40,000 Hrs

VARIATIONS

LC6514	DEX 40W Streetlight with PE Cell, Black, Non-Dim, 5700K
--------	---

dynamic series

Efficient. Cutting Edge. Reliable

