

Diomede Dx 3W

Exterior Projector Light

The Diomede Dx 3W Projector Light is available as a Surface or spike mounted, adjustable spot luminaire, anodized aluminium with tempered glass and aluminium honeycomb lens.

Dx - Spot luminaire turned anodized aluminium, silicone glued tempered glass, silicone gaskets, aluminium honeycomb, metal cable gland M12x1.5/ M10x1.45, neoprene 2 poles cables H05RN-F. Premium Quality, Italian Made product.



IP65

SPECIFICATIONS

Material Specifications

Material Anodised Aluminium, Tempered Glass

Finish Aluminium or Bronze Finish **Dimensions** 38mm (Dia) x 60mm

Ingress Protection IP65

AccessoriesStake Mounting IncludedWarranty5 Year Replacement

Electrical Specifications

Power Supply IP67 Remote Driver, Sold Separately

Max. Loading4.5WInput Voltage24V

Optic Specifications

Light Source 3W CREE LED

Optics Aluminium Honeycomb Lens

CRI 83Ra **Reported L70 (Hours)** > 54,000 Hrs

VARIATIONS

900412006 Dx 3W Projector Light 24V, Anodised Aluminium, 15°, 3000K
900412019 Dx 3W Projector Light 24V, Anodized Bronze, 36°, 3000K
900412009 Dx 3W Projector Light 24V, Anodized Aluminium, 21°, 3000K







