

NEO PRO D6.25

25W Commercial Downlight

The NEO PRO D6.25 Commercial Downlight is designed for higher ceilings, or when more focused light is required. With a smaller 175mm cut out this model boasts a 25W output. It has a direct output with a 40 degree beam angle. Available in 4000K and 3000K, dimmable and non-dimmable options are available.

Designed for use in offices, retail and public spaces.



SPECIFICATIONS

Material Specifications

Material	Die-Cast Aluminium, Tempered Glass
Colour	Powdercoated Matt White Trim
Cutout	175mm Dia
Dimensions	197mm Face Dia x 82mm (D)
Ingress Protection	IP65
Benefits	Fixing Clips allow up to 35mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Philips 27W, Constant Current 700mA
Options	DALI Available
Operating Temperature (Ta)	-20°C to +40°C
Connection Method	Australian 2-Pin Plug & 1.0m Lead

Optic Specifications

Light Source	25W LED Samsung COB with Reflector
CRI	85Ra
Colour Deviation	SDCM ≤ 3
UGR	< 19
Rated Lifetime (L70B50)	50,000 Hrs

VARIATIONS

LC5520	NEO PRO D6.25 Downlight 25W, 40°, Phase Dim, 3000K, 2300lm
LC5521	NEO PRO D6.25 Downlight 25W, 40°, Phase Dim, 4000K, 2500lm
LC5522	NEO PRO D6.25 Downlight 25W, 40°, DALI Dim, 3000K, 2300lm
LC5523	NEO PRO D6.25 Downlight 25W, 40°, DALI Dim, 4000K, 2500lm