

# SENTRY Test Switch

## Emergency Lighting

Sentry Emergency Test Switch, 4 Circuit 16A DIN Rail Mounted.

A compact, DIN-mountable Test Switch for easy installation in a switchboard, Sentry simulates mains failure for a 90 or 120 minutes duration via a user-selectable switch.

In accordance with AS2293.2, manual discharge facilities for emergency lighting installation must be key-operated and automatically reverts back to normal state upon completion of the discharge test. A 120 minute commissioning test shall be conducted for all new installations (the first discharge), followed by a 90 minute in-service discharge test every 6 months thereafter.



### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	Flame - Retardant Polycarbonate
<b>Dimensions</b>	100mm x 100mm
<b>Ingress Protection</b>	IP20
<b>Warranty</b>	3 Year Warranty

#### Electrical Specifications

<b>Mounting</b>	Din Rail
<b>Input Voltage</b>	240VAC
<b>Weight</b>	0.3Kg
<b>Operating Temperature (Ta)</b>	1°C - 40°C
<b>Mode of Operation</b>	Key-Operated

### VARIATIONS

<b>ETS-SENTRY</b>	SENTRY Emergency DIN-Rail Test Switch, White
-------------------	--