

Outreach Arm

Single



SPECIFICATIONS

Material Specifications

Finish	Hot Dip Galvanised
Dimensions	300-2000mm (L) x 220mm (H)

VARIATIONS

SOA300-76-48	Single Outreach Arm 300mm, 76mm Dia to suit 60mm spigot, w. 48mm Arm, Galv.
SOA300-76-48-PC	Single Outreach Arm 300mm, 76mm Dia to suit 60mm spigot, w. 48mm Arm, Textura Black
SOA300-76-60	Single Outreach Arm 300mm, 76mm Dia to suit 60mm spigot, with 60mm Arm, Galv.
SOA300-76-60-PC	Single Outreach Arm 300mm w. 60mm Spigot, Powdercoated, Textura Black
SOA300-89-60	Single Outreach Arm 300mm, 89mm Dia to suit 76mm Spigot, with 60mm Arm, Galv.
SOA300-102-60	Single Outreach Arm 300mm, 102mm Dia to suit 89mm Spigot, with 60mm Arm, Galv.
SOA600-60-48	Single Outreach Arm 600mm w. 48mm Spigot, Galv.
SOA600-76-60	Single Outreach Arm 600mm, 76mm Dia to suit 60mm spigot, with 60mm Arm, Galv.
SOA1000-76-48	Single Outreach Arm 1000mm, 76mm Dia to suit 60mm spigot, with 48mm Arm, Galv.
SOA1000-76-60	Single Outreach Arm 1000mm, 76mm Dia to suit 60mm spigot, with 60mm Arm
SOA1200-76-48	Single Outreach Arm 1200mm, 76mm Dia to suit 60mm spigot, with 42mm Arm, Galv.
SOA1200-76-60	Single Outreach Arm 1200mm, 76mm Dia to suit 60mm spigot, with 60mm Arm, Galv.
SOA1500-60-0	Single Outreach Arm 1500mm w. 60mm Spigot, Galv.
SOA1500-60-0-PC	Single Outreach Arm 1500mm w. 60mm Spigot, Textura Black
SOA2000-76-60	Single Outreach Arm 2000mm, 76mm Dia to suit 60mm spigot, with 60mm Arm

