Jeccolux Illuminating spaces. Inspiring growth.

Light Pole 24m Tapered Octagonal



Specifically designed to provide a stable platform for Decrolux lighting fixtures, our range of tapered octagonal poles excel at withstanding extreme winds and other weather conditions. Available in custom heights from 4.5 to 35 metres, our octagonal poles are fabricated to ensure increased stability and uninterrupted lighting no matter their height. Perfect for sporting, commercial, industrial, and other uses these towering lights can come with additional features such as climbing rungs, platforms, and lightning protection rods to ensure the ongoing safe operation and easy repair of both the pole's internal and external components.

3 section tapered pole, with 3 slip joins; 600mm & 450mm.



SPECIFICATIONS

Material Specifications

Material	Mild Steel, Hot Dip Galvanised
Finish	Galv, or Powder Coat
Dimensions	125-465mm (Dia) x 24,000mm (H)
Spigot Size	88.9mm (Dia) x 200mm (L)
Max. Top Weight	200kg
Hold Down Bolts	12 x M30 @ 640 PCD
Ultimate Base Moment	172.9kNm
Ultimate Base Shear	14.2kN
Pole Weight	971Kg
Base Plate Dimensions	740mm (Outside Dia)
Door Opening	610 × 190 (x3)

VARIATIONS

HTP240-76	Tapered Octagonal Pole 24m w. 76mm Spigot, Galv.
HTP240-89	Tapered Octagonal Pole 24m w. 89mm Spigot, Galv.
HTP240-76 -PC	Tapered Octagonal Pole 24m w. 76mm Spigot, Powder Coated
HTP240-89	Tapered Octagonal Pole 24m w. 89mm Spigot, Powder Coated

