

Light Pole 6.0m

Tapered Round



Specifically designed to provide a stable platform for Decrolux lighting fixtures our range of pipe poles excel at withstanding extreme winds and other weather conditions. Available in custom heights between 4 and 8 metres, our pipe poles are fabricated to ensure increased stability and uninterrupted lighting no matter their height.

SPECIFICATIONS

Material Specifications

Material	Mild Steel, Hot Dip Galvanised
Finish	Galv, or Powder Coat
Max. Top Weight	90kg
Ultimate Base Moment	6.5kNm
Ultimate Base Shear	1.3kN
Pole Weight	76Kg

Dimensions

Dimensions	76mm (Dia) x 6,000mm (H)
Base Plate Dimensions	233mm x 233mm
Hold Down Bolts	4 x M20 @ 233 PCD
Spigot Size	60mm/ 76mm

VARIATIONS

HTR060-60	Tapered Round Pole 6.0m Light Duty, 60mm Spigot, Galv.
HTR060-76	Tapered Round Pole 6.0m Light Duty, 76mm Spigot, Galv.
HTR060-60-PC	Tapered Round Pole 6.0m Light Duty, 60mm Spigot, Powder Coated
HTR060-76-PC	Tapered Round Pole 6.0m Light Duty, 76mm Spigot, Powder Coated
HTR060-RS	Tapered Round Pole 6.0m, Light Duty, No Base Plate, Raw Mild Steel, Mild Steel

