

KALO 25W

Commercial Downlight 150mm

The KALO 25W Commercial Downlight is used in commercial applications where style and class are important. Boasting a low profile for the output, this IP54 Rated Downlight is used in schools, hospitals, corridors and wet areas. With a matt silver reflector and diffused lens the KALO series offers excellent optical control along with visual interest.









SPECIFICATIONS

Material Specifications

MaterialHigh Grade AluminiumFinishSmooth Powder CoatDimensions160mm Dia x 100mm (H)

 Cutout
 150mm (Dia)

 Ingress Protection
 IP54

Warranty 5 Year Replacement

Electrical Specifications

Power Supply 28W Actec Phase Dim Driver

Options DALI Available

Connection Method Australian 2-Pin Plug and 1.0m Lead

Input Voltage 240V

Optic Specifications

Light Source Citizen COB LED

 Delivered Lumens
 2700lm

 CRI
 83Ra

 Beam Angle
 60°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs


 Calculated L70 (Hours)
 115,000 Hrs

VARIATIONS

LC5440KALO 25W Commercial Downlight, White, Phase Dim, 3000KLC5440BKALO 25W Commercial Downlight, Black, Phase Dim, 3000KLC5441KALO 25W Commercial Downlight, White, Phase Dim, 4000KLC5441BKALO 25W Commercial Downlight, Black, Phase Dim, 4000K







Ø160

10

