

# **KINGSTON 300W**

# Architectural Streetlight

The KINGSTON 300W Roadway Lighting Series is powered by the Crystal OpticLED platform, and features innovative thermal management design, offering exceptional performance and value. This versatile luminaire can be tailored to the unique specifications of each project. Tool Free Opening Clip, allowing for Top Opening Easy Maintenance. The KINGSTON Streetlight Series is fitted with knife switch safety feature to cut off power supply when the device is open.





**IP66** 



#### **SPECIFICATIONS**

#### **Material Specifications**

**Housing** High Pressure Die-Cast Aluminium Alloy, Clear

Tempered Glass

FinishPolyester Powder Coat, Signal BlackDimensions793mm(L) x 300mm(W) x 109mm(H)

 Spigot Size
 60mm

 Ingress Protection
 IP66

 Impact Rating
 IK10

 Weight
 9.2kg

 Mounting Height
 10m - 12m

Warranty 5 Year Replacement

#### **Electrical Specifications**

Power Supply 320W Integrated Driver Input Voltage 240VAC, 50/60Hz
Operating Temperature (Ta) -20°C to +55°C

### **Optic Specifications**

**Light Source** Phillips LED SMD 5050 x 192

**Delivered Lumens** 42,600lm - 46,257lm

CRI 79Ra

 Reported L70 (Hours)
 > 54,000 Hrs

 Calculated L90 (Hours)
 49,000 Hrs

 Calculated L70 (Hours)
 79,000 Hrs

## VARIATIONS

 LC6180-T2
 KINGSTON 300W Streetlight, Signal Black, T2, 4000K, 42,600lm

 LC6180-T3
 KINGSTON 300W Streetlight, Signal Black, T3, 4000K, 43,107lm

 LC6180-T4
 KINGSTON 300W Streetlight, Signal Black, T4, 4000K, 46,257lm







