


LINX 11W

Linear Downlight Fixed

Classic Series

Proven. Quality. Customisable

The LINX 11W Linear Recessed Downlight is an ultra-compact LED marvel. Experience unparalleled glare control with its lens and reflector fusion. Boasting a five module, linear light design and high CRI, it radiates commercial-quality brilliance. Choose between 24 or 40° beam angles to suit your needs. The secondary reflector is available in black, white, silver, and gold options. With a five year warranty, illuminate your space with confidence and elegance.



Verified by Techlume Australia on 09/03/2023




IP40



SPECIFICATIONS

Material Specifications

Material	High Grade Aluminium
Colour	White / Black Insert Options
Ingress Protection	IP40
Dimensions	152mm(L) x 45mm(W) x 60mm(D)
Cutout	144mm x 37mm
Warranty	5 Year Replacement



Electrical Specifications

Power Supply	Actec 13W Driver 700mA, Phase Dim
System Watts	12.5W - 12.7W
Connection Method	Australian 2-Pin Plug & 1.0m Lead
Input Voltage	240V

Optic Specifications

Light Source	Osram 11W SMD LED
Delivered Lumens	987lm - 1053lm
Efficacy	>78lm/W
Beam Angle	24° / 40°
CRI	>90Ra
Colour Deviation	SDCM ≤ 3
UGR	<19
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC4470	LINX 11W Linear Fixed Downlight, White w. Black Insert, 40°, Phase Dim, 3000K, 987lm
LC4470B	LINX 11W Linear Fixed Downlight, Black w. Black Insert, 40°, Phase Dim, 3000K, 1024lm
LC4471	LINX 11W Linear Fixed Downlight, White w. Black Insert, 40°, Phase Dim, 4000K, 1053lm
LC4471B	LINX 11W Linear Fixed Downlight, Black w. Black Insert, 40°, Phase Dim, 4000K, 1053lm