

TITAN 20W

dynamic series Efficient. Cutting Edge. Reliable

Weatherproof Emergency Batten 650mm

The TITAN 20W Emergency Batten 650mm has been introduced as a premium quality batten, high-efficiency, and very easy to install. Polycarbonate body with durable seal and clear polycarbonate lens. Resists impact (IK08) and IP66 - designed for harsh environments. Excellent for Commercial applications including schools, car parks, security purposes, and public buildings. The robust construction shields the high output LED technology to maintain maximum light output and lamp life.

SS316 Clips available.











SPECIFICATIONS

Material Specifications

Housing Grey Moulded PC Body, Clear PC Diffuser

Material 304 Stainless Clips

Dimensions 650mm(L) x 97mm(W) x 82mm(H)

Impact RatingIK08Ingress ProtectionIP66Weight1.3kg

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Tridonic 25W Non-Dim Driver 350mA (Internal)

Input Voltage 240V 50/60Hz

Connection Method 20mm Cable Gland at One end. 3 knock-out

points in rear, and $1\,\mathrm{in}$ side.

Operating Temperature (Ta) -20°C to +40°C

Optic Specifications

Light Source LG LEMWS28R80 Series

 Delivered Lumens
 2140 lm

 CRI
 > 80 Ra

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

 Calculated L70 (Hours)
 134,000 Hrs

 AS2293 Classification
 C0:D40, C90:D20


VARIATIONS

LC5314 TITAN 20W Emergency Weatherproof Batten 650mm, 120°, Non-Dim,

4000K

LC5314D TITAN 20W Emergency Weatherproof Batten 650mm, 120°, DALI,

4000K





1300 827 284 sales@decrolux.com.au | Latest Product Data >