

TITAN 20W

Weatherproof Batten 1220mm

dynamic series
Efficient. Cutting Edge. Reliable

The TITAN Weatherproof batten has been introduced as a premium quality batten, high-efficiency, and very easy to install. IP66, designed for harsh environments. Stainless Steel 316 Clips available.

The TITAN 20W Weatherproof Batten 1220mm is a low output linear light, for low mounting heights, or where low lux levels are required.









SPECIFICATIONS

Material Specifications

Housing Grey Moulded PC Body, Clear PC Diffuser

Material 304 Stainless Clips

Impact RatingIK08Ingress ProtectionIP66

Dimensions $1220 \text{mm(L)} \times 97 \text{mm(W)} \times 82 \text{mm(H)}$

Weight 1.7kg

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Tridonic 24W Non-Dim Driver 500mA (Internal)

Input Voltage 240 V 50/60 Hz
Operating Temperature (Ta) -20 °C to +40 °C

Connection Method 20mm Cable Gland at One end. 3 knock-out

points in rear, and 1 in side.

Optic Specifications

Light Source 20W LED Samsung SMD 2835

 Delivered Lumens
 2382lm

 CRI
 80Ra

 Beam Angle
 120°

 Reported L70 (Hours)
 > 54,00

 Reported L70 (Hours)
 > 54,000 Hrs

 Calculated L70 (Hours)
 134,000 Hrs

VARIATIONS

LC5312 TITAN 20W Weatherproof Batten, 1220mm, Non-Dim, 4000K, 2382lm

LC5307 TITAN 20W Weatherproof Batten 1220mm, w. Motion Sensor, 4000K,

2382lm





