decrolux

1300 827 284 www.decrolux.com.au

WALTZ 30W Rectangle Downlight

The WALTZ 30W rectangle downlight is a gyro design. It adopted Citizen COB and a high transmittance rate lens to keep high light efficiency. ADC12 Aluminum profile provides excellent thermal dissipation. Modular design with reflector type and lens type options. Rectangle shape with two heads. The luminaire is tilted 25° in all directions (360°), perfectly meet the demands of different lighting angles. Beam angles available are 36° or 60°.



SPECIFICATIONS

Material Specifications

Material Colour Warranty Dimensions Cutout Ingress Protection Impact Rating

Electrical Specifications

Power Supply Operating Temperature (Ta) Input Voltage Remote Driver, 500mA, Flicker Free -20°C to +45°C 240V

Premium Grade Aluminum

5 Year Replacement

255 x 95 x 53m 249mm x 89mm


IP54

IK06

Powdercoated Matt White / Black

Optic Specifications

Light Source Delivered Lumens CRI Beam Angle Reported L70 (Hours) 3 x Citizen 10W COB LED 3000lm >80 60° > 54,000 Hrs



VARIATIONS

LC3432B	WALTZ Triple 3x10W Rectangle Downlight, Black, 60°, Phase Dim, 2700K
LC3430W	WALTZ Triple 3x10W Rectangle Downlight, White, 60°, Phase Dim, 3000K
LC3430B	WALTZ Triple 3x10W Rectangle Downlight, Black, 60°, Phase Dim, 3000K
LC3431W	WALTZ Triple 3x10W Rectangle Downlight, White, 60°, Phase Dim, 4000K
LC3431B	WALTZ Triple 3x10W Rectangle Downlight, Black, 60°, Phase Dim, 4000K

B and a rofile d lens II



dynamic series

Efficient. Cutting Edge. Reliable

Product design and technical data may be subject to change without prior notice.
Generated 4th May 2024 - © Decrolux

